



DC-Custom Series

User's manual

Important notes

■ Operation

This product is a power supply cable for 9 VDC. Please use center minus polarity device.

Please turn off the power and refrain using when an earthquake and/or lightning occurs.

Please turn off the power supply before connecting the effector and power supply. Please turn off the power supply before disconnecting it before removing it.

■ Cautions

Please refrain from using in places like the following. It may cause discoloration, deformation or noise.

- Places exposed to direct sunlight.
- Close to a magnetism device.
- Places where it gets hot and humid.
- Devices with different voltage specifications and different inlets.
- Unstable place.

■ Notes

- Do not use it for applications other than DC cable.
- Do not modify or disassemble.
- Do not pull by force, and do not excessively bend.
- Please check the polarity and size of your existing equipment before use.
- Do not touch with wet hands or spray water.

specifications

DC-Custom

DC-Custom-Pure


Length	20cm, 50cm, 80cm
Rating	Max. Operating Voltage - UL:300V RMS Max. recommended Current - 2.8 Amps per Conductor @25°C
Plug size	2.1mm

DC-Custom-FULL


Length	20cm, 50cm, 80cm
Rating	Max. Operating Voltage - UL:300V RMS Max. recommended Current - 2.9 Amps per Conductor @25°C
Plug size	2.1mm

feature

DC-Custom



DC-Custom-Pure



DC-Custom-FULL

